

PRODUCT-DETAILS

6845/11 AGM-204

6845/11 AGM-204 Standard Devices



Informations générales

Extension du type de produit	6845/11 AGM-204
Code de produit	2CKA006800A2330
EAN	4011395079003
Description courte	6845/11 AGM-204 Standard Devices
Description longue	Electronic movement detector for detecting thermal motion. With display for detection and operation mode. With ground and rear-field detection. With planar compensation: $\pm 30^\circ$. With high-quality lens for optimum detection. Detection sensitivity selectable in 3 steps. Surveillance density: 84 sectors with 336 switching segments. All functions controlled by microprocessor. Always-On (4 hours) and Presencesimulation can be activated via IR-remote control. With automatic range stabilization. With automatic interference suppression. With automatic dazzle-proofing. With brightness-independent test mode for evaluating the detection zone. Additional possibility for switch-on via normally open push-button switch. Switch-off delay: 10 sec to 30 min or short-time pulse 1 sec adjustable.

Technique

Tension nominale (U_r)	230 V
Auxiliary Voltage AC/DC	230 V AC/DC
Type de tension	AC
Courant nominal (I_n)	16 A
Current Range	Maximum 80 A Minimum 0.01 A
Fréquence (f)	50...60 Hz
Fréquence assignée (f)	50...60 Hz
Maximum Switching Power	3680 W

Power Loss	1 W
Plage de mesure	Diameter Detection range on floor 32 m
Nombre de sorties	1
Number of Switching Zones	1
Product Range	Movement detector
Délai (T)	Off 0 second [unit of time] On 0 second [unit of time]
Minimum Switching Time	Switch-On 10 second [unit of time]
Type de raccordement	Cable Clamp
Type de charge	ohmic, capacitive and inductive loads
Type de montage	Surface Mounted
Sensor Type	Passive infrared
Finition de surface	Surface protection: Untreated Surface finishing: Matt
Matériau	Material quality: Thermoplastic (3) Material: Plastic (3)
Flux lumineux	0...1000 lx
Model Number	Movement sensor
RAL Number	RAL 9010 - Blanc pur
Couleur	Alpine white
Poids de la batterie	0 g
Nombre de batteries	0

Environnement

Température de l'air ambiant	Operation -25 ... +55 °C
Indice de protection	IP55
Statut RoHS	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Dimensions

Produit Largeur Net	97 mm
Produit Hauteur Net	102 mm
Produit Longueur Net	105 mm
Poids net	0.185 kg
Profondeur d'encastrement (t ₂)	0 mm

Emballage

Emballage Niveau 1 Unités	carton 1 pièce
Emballage Niveau 1 Largeur	100 mm
Emballage Niveau 1 Hauteur	89 mm
Emballage Niveau 1 Longueur	179 mm
Emballage Niveau 1 Poids	0.32 kg
Emballage Niveau 1 EAN	4011395079003
Emballage Niveau 2 Unités	10 pièce
Emballage Niveau 2 Largeur	368 mm

Emballage Niveau 2 Hauteur	102 mm
Emballage Niveau 2 Longueur	510 mm
Emballage Niveau 2 Poids	3.6 kg
Emballage Niveau 3 Unités	360 pièce
Emballage Niveau 3 Largeur	0.8 m
Emballage Niveau 3 Hauteur	0.107 m
Emballage Niveau 3 Longueur	1.2 m
Emballage Niveau 3 Poids	149.6 kg

Commande

Quantité minimum	1 pièce
Code douanier	85365080
Pays d'origine	Germany (DE)

Certificats et Déclarations (Numéro de document)

Déclaration de Conformité - CE	2CKA100000E1936
Instructions et manuels	DEBJE-ba_0373_1_6539_6845-Man
REACH Declaration	2CKA309999E9999
Informations RoHS	9AKK104295D8727

Popular Downloads

Fiche produit, informations techniques	No document needed
Instructions et manuels	DEBJE-ba_0373_1_6539_6845-Man

Classifications

ETIM 7	EC000133 - Movement sensor complete
ETIM 8	EC000133 - Movement sensor complete
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
DEEE B2C / B2B	Business To Consumer
CN8	8536 50 80
eClass	V11.0 : 27144007

Catégories

Produits basse tension → StandAlone Electronics → Outdoor Movement Detector → ProfessionalLINE Series → Standard Devices → Watchdog 220 ProfessionalLINE

