Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: OSRA

Supplier's address: LEDVANCE GmbH, Parkring 33, Garching, Germany

Model identifier: AC34206

Tvi	рe	of	lig	ht	SO	urce	:
. , ,		•	о		-		•

Lighting technology used: CFLni Non-directional or directional: Light source cap-type (or other electric interface) Mains or non-mains: NMLS Connected light source (CLS): Colour-tuneable light source: No Envelope: Anti-glare shield: No Dimmable: No	Droduct norometers					
directional: Light source cap-type G24d-2 (or other electric interface) Mains or non-mains: NMLS Connected light source (CLS): Colour-tuneable light source: No Envelope:	Anti-glare shield:	No	Dimmable:	No		
directional: Light source cap-type (or other electric interface) Mains or non-mains: NMLS Connected light source (CLS):	High luminance light source:	No				
directional: Light source cap-type G24d-2 (or other electric interface) Mains or non-mains: NMLS Connected light No	Colour-tuneable light source:	No	Envelope:	-		
directional: Light source cap-type G24d-2	Mains or non-mains:	NMLS		No		
directional:	(or other electric interface)					
	Light source cap-type	G24d-2				
	Lighting technology used:	CFLni	Non-directional or directional:	NDLS		

Product parameters

Parameter		Value	Parameter	Value
General product parameters:				
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		19	Energy efficiency class	G
dicating if it refe a sphere (360°)	s flux (фuse), in- ers to the flux in , in a wide cone arrow cone (90º)	1 200 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power (P _{on}), expressed in W		18,8	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimensions without	Height	153	Spectral power dis-	See image
	Width	12	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	12	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,380 0,380

(a)'-': not applicable; (b)'-': not applicable;

