## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: LEDVANCE GmbH, Parkring 33, Garching, Germany

Model identifier: AC35299

| Lighting technology used:     | other | Non-directional or directional: | NDLS |  |  |
|-------------------------------|-------|---------------------------------|------|--|--|
| Light source cap-type         | G4    |                                 |      |  |  |
| (or other electric interface) |       |                                 |      |  |  |
| Mains or non-mains:           | NMLS  | Connected light source (CLS):   | No   |  |  |
| Colour-tuneable light source: | No    | Envelope:                       | -    |  |  |
| High luminance light source:  | No    |                                 |      |  |  |
| Anti-glare shield:            | No    | Dimmable:                       | Yes  |  |  |
| Product parameters            |       |                                 |      |  |  |

| Product parameters   |                                     |                         |  |              |  |  |
|--|-------------------------------------|-------------------------|--|--------------|--|--|
| Parameter  |                                     | Value                   | Parameter  | Value        |  |  |
| General product parameters:  |                                     |                         |  |              |  |  |
| Energy consummode (kWh/10 up to the neares                               | 00 h), rounded                      | 20                      | Energy efficiency<br>class   | G            |  |  |
| Useful luminous dicating if it refer a sphere (360°) (120°) or in a na   | ers to the flux in , in a wide cone | 300 in<br>Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 800        |  |  |
| On-mode pow<br>pressed in W  | ver (P <sub>on</sub> ), ex-         | 20,0                    | Standby power (P <sub>sb</sub> ),<br>expressed in W and<br>rounded to the sec-<br>ond decimal  | 0,00         |  |  |
| Networked st<br>(P <sub>net</sub> ) for CLS, e<br>and rounded to<br>imal | •                                   | -                       | Colour rendering in-<br>dex, rounded to the<br>nearest integer, or<br>the range of CRI-val-<br>ues that can be set   | 100          |  |  |
| Outer dimen-   | Height                              | 33                      | Spectral power dis-  | See image    |  |  |
| sions without  | Width                               | 10                      | tribution in the   | in last page |  |  |
| separate con-<br>trol gear, light-<br>ing control                        | Depth                               | 10                      | range 250 nm to 800<br>nm, at full-load  |              |  |  |

| parts and non-<br>lighting con-<br>trol parts, if<br>any (millime-<br>tre) |   |                                    |                |
|--|---|------------------------------------|----------------|
| Claim of equivalent power <sup>(a)</sup>                                   | - | If yes, equivalent power (W)       | -              |
|  |   | Chromaticity coordinates (x and y) | 0,452<br>0,409 |

(a)'-': not applicable; (b)'-': not applicable;

