

PRODUCT DATASHEET

HALOLINE PRO 80 W 230 V R7S

HALOLINE® PRO | Double ended halogen lamps with tube base



Areas of application

- General illumination
- Entrance lighting
- Pathway lighting
- Outdoor applications only in suitable luminaires
- Traffic areas
- Shops
- Restaurants, hotels and similar prestigious applications
- Offices, public buildings
- Ideal for emphasizing and accentuating the structure of a room

Product benefits

- Brilliant accent lighting
- Direct replacement for standard tubular halogen lamps
- Significantly lower CO₂ emissions compared to standard version
- Lower thermal output (compared with the standard reference product)
- No transformer required
- Contains no mercury

Product features

- Average life: 2,000 h
- Dimmable
- Color rendering index R_a: 100




TECHNICAL DATA

Electrical data

Nominal wattage	80 W
Construction wattage	80.00 W
Nominal voltage	230 V
Claimed equiv. conventional lamp power	100 W
Power factor λ	1.00

Photometrical data

Luminous flux	1400 lm
Luminous efficacy	17 lm/W
Light color (designation)	Warm White
Color temperature	2900 K
Color rendering index Ra	100
Light color	1029
UV protection	No



Light technical data

Starting time	0 s
---------------	-----

Dimensions & Weight

Overall length	74.90 mm
Diameter	12.00 mm
Product weight	5.6 g

Lifespan

Lifespan	2000 h
----------	--------

Additional product data

Base (standard designation)	R7s
Mercury-free	Yes
Design / version	Tube
Product remark	Fuse protection with indicated values recommended acc. to IEC60357, EN60357 / For outdoor applications and operation in damp locations special approved fixtures are required

Capabilities

Dimmable	Yes
Burning position	Any

Certificates & Standards

Energy efficiency class	G
Energy consumption	80.00 kWh/1000h

Country-specific categorizations

ILCOS	HDG-80-230-R7s-74,9
Order reference	64690 ECO

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	OTHER
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	R7s
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	74.90 mm
Height	12.00 mm
Width	12.00 mm
Chromaticity coordinate x	0.444
Chromaticity coordinate y	0.406
Beam angle correspondence	SPHERE_360

EPREL ID	714451
Model number	AC35302,AC35302,AC35302

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321928078	Folding box 1	87 mm x 18 mm x 21 mm	6.00 g	0.03 dm ³
4058075308732	Shipping box 15	93 mm x 71 mm x 90 mm	234.00 g	0.59 dm ³
4008321327758	Shipping box 20	112 mm x 77 mm x 92 mm	209.00 g	0.79 dm ³
4058075308749	Shipping box 60	195 mm x 148 mm x 97 mm	1086.00 g	2.80 dm ³
4052899401129	Shipping box 720			

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

