Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LEDVANCE

Supplier's address: LEDVANCE GmbH, Parkring 33, Garching, Germany

Model identifier: AC33722

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS		
Light source cap-type	GU5.3				
(or other electric interface)					
Mains or non-mains:	NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	Yes		
Product parameters					

Parameter		Value	Parameter	Value			
General product parameters:							
Energy consum mode (kWh/10 up to the neares	00 h), rounded	6	Energy efficiency class	G			
dicating if it refe a sphere (360°)	s flux (φuse), in- ers to the flux in , in a wide cone rrow cone (90º)	350 in Nar- row cone (90°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set	3 000			
On-mode pow pressed in W	ver (P _{on}), ex-	4,9	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00			
	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	90			
Outer dimen-	Height	46	Spectral power dis-	See image			
sions without separate con- trol gear, light- ing control	Width Depth	510 510	tribution in the range 250 nm to 800 nm, at full-load	in last page			

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	35		
		Chromaticity coordi-	0,434		
		nates (x and y)	0,403		
Parameters for directional light sources:					
Peak luminous intensity (cd)	560	Beam angle in de- grees, or the range of beam angles that can be set	36		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	0	Survival factor	0,50		
the lumen maintenance factor	0,70				
(a),	1				

(a)'-' : not applicable;

(b)'-' : not applicable;

