

PRODUCT-DETAILS

DDA202 A S-63/0.1

DDA202 A S-63/0.1 Residual Current Device Block



Informations générales

Extension du type de produit	DDA202 A S-63/0.1
Code de produit	2CSB202201R2630
EAN	8012542799306
Description courte	DDA202 A S-63/0.1 Residual Current Device Block
Description longue	The RCD block DDA200 series is suitable for assembly with MCBs S200 series. It assures protection against the effects of sinusoidal alternating and direct pulsating earth fault currents with an intentional tripping delay, in order to realize the selectivity with downstream instantaneous devices. Applications: commercial, industrial.

Technique

Normes et standards	IEC/EN 61009 Ann. G
Type of Residual Current	A type
Tension nominale (U_r)	230/400 V
Tension	230 V
Tension assignée d'isolement (U_i)	500 V
Tension assignée de tenue aux chocs (U_{imp})	4 kV
Courant nominal (I_n)	63 A
Rated Residual Current	100 mA

Maximum Surge Current	5 kA
Leakage Current Type	A
Fréquence assignée (f)	50/60 Hz
Power Loss	5 W
Power Supply Connection	Arbitrary
Electrical Endurance	10000 cycle
Nombre de pôles	2
Operating Characteristic	Selective
Options Provided	-
Connecting Capacity	Rigid 25 ... 25 mm² Flexible 25 ... 25 mm²

Environnement

Température extérieure	-25...55 °C
Température de l'air ambiant	Operation -25...55 °C
Indice de protection	IP2X
Resistance to Vibrations acc. to IEC 60068-2-6	0.1 mm or 1 g - 20 cycles at 5...150...5 Hz
Resistance to Shock acc. to IEC 60068-2-27	25g / 2 shocks / 13 ms
RoHS Status	Following EU Directive 2011/65/EU
Environmental Information	Refer to RoHS

Technique UL/CSA

Short-Circuit Current Rating (SCCR)	0.1 ... 0.1 A
-------------------------------------	---------------

Dimensions

Produit Largeur Net	70 mm
Produit Hauteur Net	93 mm
Produit Longueur Net	76 mm
Poids net	0.210 kg

Emballage

Emballage Niveau 1 Unités	box 1 pièce
Emballage Niveau 1 Largeur	79 mm
Emballage Niveau 1 Hauteur	80 mm
Emballage Niveau 1 Longueur	104 mm
Emballage Niveau 1 Poids	0.245 kg
Emballage Niveau 1 EAN	8012542799313

Commande	
Quantité minimum	1 pièce
Code douanier	85363030
Pays d'origine	Italy (IT)

Certificats et Déclarations (Numéro de document)	
Déclaration de Conformité - CE	9AKK106713A5614
Environmental Information	Refer to RoHS
Instructions et manuels	2CSB423001D003
RoHS Information	2CSC427001K2701

Popular Downloads	
Fiche produit, informations techniques	9AKK107991A8329
Instructions et manuels	2CSB423001D003

Classifications	
ETIM 7	EC002297 - Residual current circuit breaker (RCCB) module
ETIM 8	EC002297 - Residual current circuit breaker (RCCB) module
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
DEEE B2C / B2B	Business To Consumer
CN8	85363030
Object Classification Code	F

Catégories

Produits basse tension → Appareillage modulaire et parafoudres → Protection différentielle → Blocs différentiels

