

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** LEDVANCE

**Supplier's address:** LEDVANCE GmbH, Parkring 33, Garching, Germany

**Model identifier:** AC35311

**Type of light source:**

|   |       |                                 |      |
|---|-------|---------------------------------|------|
| Lighting technology used:                           | other | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | G4    |                                 |      |
| Mains or non-mains:                                 | NMLS  | Connected light source (CLS):   | No   |
| Colour-tuneable light source:                       | No    | Envelope:                       | -    |
| High luminance light source:                        | No    |                                 |      |
| Anti-glare shield:                                  | No    | Dimmable:                       | Yes  |

## Product parameters

| Parameter   | Value               | Parameter  | Value                  |
|---|---------------------|--|------------------------|
| <b>General product parameters:</b>  |                     |  |                        |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer   | 5                   | Energy efficiency class  | G                      |
| Useful luminous flux ( $\phi_{\text{use}}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 55 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 700                  |
| On-mode power ( $P_{\text{on}}$ ), expressed in W   | 5,0                 | Standby power ( $P_{\text{sb}}$ ), expressed in W and rounded to the second decimal  | 0,00                   |
| Networked standby power ( $P_{\text{net}}$ ) for CLS, expressed in W and rounded to the second decimal  | -                   | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 100                    |
| Outer dimensions without separate control gear, lighting control  | Height              | Spectral power distribution in the range 250 nm to 800 nm, at full-load  | See image in last page |
|   | Width               |  |                        |
|   | Depth               |  |                        |

|   |   |                                    |                |  |
|---|---|------------------------------------|----------------|--|
| parts and non-lighting control parts, if any (millimetre) |   |                                    |                |  |
| Claim of equivalent power <sup>(a)</sup>                  | - | If yes, equivalent power (W)       | -              |  |
|   |   | Chromaticity coordinates (x and y) | 0,460<br>0,411 |  |

(a) : not applicable;

(b) : not applicable;

