



BE PA25 2xUTP6+TRI6-HI R1

Pref 25mm+2xU/UTP CAT6 Eca+Telenet/Voo Ind Hirschm B2ca R100

Properties of the article

◦ Articlenumber	1234001503
◦ Barcode	5420056254281
◦ Category	Tv & Music
◦ Gross weight (kg)	21.0
◦ Dimensions (WxLxH)	500 x 500 x 200 MM
◦ Packaging	Roll
◦ Length	100

Properties of the Preflex® tube

◦ Material of tube	Halogen-free Polypropylene
◦ Color	Purple
◦ Outer diameter (mm)	25
◦ Inner diameter (mm)	18.3
◦ Classification	ICTA 3422
◦ Pressure resistance	750N / 23°C
◦ Impact resistance	6J / -5°C
◦ Breakthrough test	2000V / 50-60 Hz 15min.
◦ Insulation resistance	min. 100 Mohm/80cm
◦ Test temperature	-5°C tot +90°C
◦ Min. installation temperature	-5°C

Characteristics of the cable or cable combination

	U/UTP CAT6	U/UTP CAT6
	COAX	
	Telenet/Voo	
	Indoor	
	HIRSCHMANN	
◦ Cable type		
◦ Color		
◦ Insulation		
◦ CPR Class	eca	

Certificates

◦ Norm van de buis	EN 61386-1, EN 61386-22, EN 60423; EN 61034, EN 60754-1, EN 60754-2
◦ Norm van de kabel	EN 50575

Certificates

