

PRODUCT-DETAILS

TM30/24

TM30/24 Fail safe bell transformer



Algemene informatie

Type	TM30/24
Artikelnummer	2CSM228765R0802
EAN	8012542287650
Omschrijving	TM30/24 Fail safe bell transformer
Omschrijving	These transformers, with safety extremely-low voltage secondary (SELV), are suitable for driving loads that call for a discontinuous supply.

Technical

Primaire spanning	230 V
Secundaire spanning	1 12 V 2 24 V
Secundaire stroom	Amperage 2 1.25 A Amperage 1 2.5 A
Maximale uitgangsstroom (I_{out})	2.5 A
Vermogensverlies	3 W
Stroomvoorziening	30 V·A
Nominaal uitvoervermogen	30 W
Geleverde opties	None

Environmental

RoHS-status

Following EU Directive 2002/95/EC August 18, 2005 and amendment

Dimensions

Breedte in module-eenheden	3
Product netto breedte	52.5 mm
Product netto hoogte	0.085 m
Product netto diepte	0.065 m
Product netto gewicht	0.450 kg
Product netto lengte	65 mm

Container Information

Pakketniveau 1 Units	box 4 stuk
Pakketniveau 1 Breedte	0.09 m
Pakketniveau 1 Hoogte	0.08 m
Pakketniveau 1 Lengte	0.054 m
Pakketniveau 1 Brutogewicht	1.8 kg
Pakketniveau 1 EAN	8012542287667

Ordering

Minimale bestelhoeveelheid	1 stuk
Nummer douanetarief	85043121
Land van herkomst	Romania (RO)

Certificates and Declarations (Document Number)

Conformiteitsverklaring - CE	9AKK106713A5640
Instructies en handleidingen	No document needed
RoHS-informatie	2CSC446004K0201

Popular Downloads

Gegevensblad, technische informatie	2CSC000001D0202
Instructies en handleidingen	No document needed

Classifications

ETIM 7	EC001547 - Bell transformer
ETIM 8	EC001547 - Bell transformer
WEEE-categorie	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85043121
Object classificatiecode	T

Categorieën

Laagspanningsproducten en -systemen → Modulaire DIN rail producten → Command and Signalling Devices → Bells and safety transformers

