



BE PA25 E 2xUTP5E+TRI6 R1

Preflex 25mm+2xU/UTP Eca CAT5E+Telenet/Voo Indoor Cca R100

Properties of the article

◦ Articlenumber	1234001493
◦ Barcode	5420056254229
◦ Category	Tv & Music
◦ Gross weight (kg)	21.5
◦ Dimensions (WxLxH)	500 X 500 X 200 MM
◦ Packaging	Roll
◦ Length	100

Properties of the Preflex® tube

◦ Material of tube	Halogen-free Polypropylene
◦ Color	Purple
◦ Outer diameter (mm)	25
◦ Inner diameter (mm)	18.3
◦ Classification	ICTA 3422
◦ Pressure resistance	750N / 23°C
◦ Impact resistance	6J / -5°C
◦ Breakthrough test	2000V / 50-60 Hz 15min.
◦ Insulation resistance	min. 100 Mohm/80cm
◦ Test temperature	-5°C tot +90°C
◦ Min. installation temperature	-5°C

Characteristics of the cable or cable combination

	U/UTP CAT5E	U/UTP CAT5E
	COAX	
	Telenet/Voo	
	Indoor	
◦ Cable type		
◦ Color		
◦ Insulation		
◦ CPR Class	eca	

Certificates

◦ Norm van de buis	EN 61386-1, EN 61386-22, EN 60423; EN 61034, EN 60754-1, EN 60754-2
◦ Norm van de kabel	EN 50575

Certificates

