



BE LGN20 LS C XGB 3G2,5 R1

Preflex SAFE 20mm+XGB Cca (a1d2s1) 3G2,5 C100

Properties of the article

◦ Articlenumber	1234001047
◦ Barcode	5420056259705
◦ Category	Energy & Light
◦ Gross weight (kg)	23.1
◦ Dimensions (WxLxH)	500 x 500 x 200 MM
◦ Packaging	Roll
◦ Length	100

Properties of the Preflex[®] tube

◦ Material of tube	Halogen-free Polypropylene
◦ Color	Light Green
◦ Outer diameter (mm)	20
◦ Inner diameter (mm)	14.1
◦ Classification	ICTA 3422
◦ Pressure resistance	750N / 23°C
◦ Impact resistance	6J / -5°C
◦ Breakthrough test	2000V / 50-60 Hz 15min.
◦ Insulation resistance	min. 100 Mohm/80cm
◦ Test temperature	-5°C tot +90°C
◦ Min. installation temperature	-5°C

Characteristics of the cable or cable combination

◦ Cable type	XGB 3G2.5
◦ Color	
◦ Insulation	LS0H
◦ CPR Class	cca s1 d2 a1

Certificates

◦ Norm van de buis	EN 61386-1, EN 61386-22, EN 60423; EN 61034, EN 60754-1, EN 60754-2
◦ Norm van de kabel	EN 50575:2014 + A1:2016; EN 13501-6:2014

Certificates

