



BE LGN16 LS C KNX/EIB 2x2x0,8 R1

Preflex SAFE 16mm+KNX (EIB) LS0H Cca (a1d2s1) 2X2X0.8mm C100

Properties of the article

◦ Articlenumber	1234001324
◦ Barcode	5420056257350
◦ Category	Data
◦ Gross weight (kg)	11.2
◦ Dimensions (WxLxH)	500 x 500 x 200 MM
◦ Packaging	Roll
◦ Length	100

Properties of the Preflex[®] tube

◦ Material of tube	Halogen-free Polypropylene
◦ Color	Light Green
◦ Outer diameter (mm)	16
◦ Inner diameter (mm)	10.6
◦ Classification	ICTA 3422
◦ Pressure resistance	750N / 23°C
◦ Impact resistance	6J / -5°C
◦ Breakthrough test	2000V / 50-60 Hz 15min.
◦ Insulation resistance	min. 100 Mohm/80cm
◦ Test temperature	-5°C tot +90°C
◦ Min. installation temperature	-5°C

Characteristics of the cable or cable combination

◦ Cable type	KNX/EIB LS0H 2x2x0.8mm
◦ Color	
◦ Insulation	LS0H
◦ CPR Class	cca s1 d1 a1

Certificates

◦ Norm van de buis	EN 61386-1, EN 61386-22, EN 60423; EN 61034, EN 60754-1, EN 60754-2
◦ Norm van de kabel	EN 60754-2 ; EN 61034 ; EN 50575 Cca s1d1a1

Certificates

