



BE LGN16 LS C Alarm 6x0,22+2x0,75 R1

Preflex SAFE 16mm+Alarm LS0H Cca (a1d2s1) 6x0.22+2x0.75 C100

Properties of the article

◦ Articlenumber	1234001190
◦ Barcode	5420056260428
◦ Category	Alarm
◦ Gross weight (kg)	7.7
◦ Dimensions (WxLxH)	500 X 500 X 200 MM
◦ Packaging	Roll
◦ Length	100

Properties of the Preflex® tube

◦ Material of tube	Halogen-free Polypropylene
◦ Color	Light Green
◦ Outer diameter (mm)	16
◦ Inner diameter (mm)	10.6
◦ Classification	ICTA 3422
◦ Pressure resistance	750N / 23°C
◦ Impact resistance	6J / -5°C
◦ Breakthrough test	2000V / 50-60 Hz 15min.
◦ Insulation resistance	min. 100 Mohm/80cm
◦ Test temperature	-5°C tot +90°C
◦ Min. installation temperature	-5°C

Characteristics of the cable or cable combination

	Alarm LS0H	
	6x0.22	2x0,75
◦ Cable type		
◦ Color		
◦ Insulation	LS0H	
◦ CPR Class	cca s1 d1 a1	

Certificates

◦ Norm van de buis	EN 61386-1, EN 61386-22, EN 60423; EN 61034, EN 60754-1, EN 60754-2
◦ Norm van de kabel	EN 60754-2 ; EN 61034 ; EN 50575 Cca s1d1a1

Certificates

