

PRODUCT-DETAILS

6845/11 AGM-204

6845/11 AGM-204 Standard Devices



Algemene informatie

Type	6845/11 AGM-204
Artikelnummer	2CKA006800A2330
EAN	4011395079003
Omschrijving	6845/11 AGM-204 Standard Devices
Omschrijving	Electronic movement detector for detecting thermal motion. With display for detection and operation mode. With ground and rear-field detection. With planar compensation: +/- 30°. With high-quality lens for optimum detection. Detection sensitivity selectable in 3 steps. Surveillance density: 84 sectors with 336 switching segments. All functions controlled by microprocessor. Always-On (4 hours) and Presencesimulation can be activated via IR-remote control. With automatic range stabilization. With automatic interference suppression. With automatic dazzle-proofing. With brightness-independent test mode for evaluating the detection zone. Additional possibility for switch-on via normally open push-button switch. Switch-off delay: 10 sec to 30 min or short-time pulse 1 sec adjustable.

Technical

Toegekende spanning (U _r)	230 V
Hulpspanning AC/DC	230 V AC/DC
Ingangsspanningstype	AC
Toegekende stroom (I _n)	16 A
Stroombereik	Maximum 80 A Minimum 0.01 A
Frequentie (f)	50...60 Hz
Toegekende frequentie (f)	50...60 Hz

Maximaal schakelvermogen	3680 W
Vermogensverlies	1 W
Meetbereik	Diameter Detection range on floor 32 m
Aantal uitgangen	1
Aantal schakelzones	1
Productreeks	Movement detector
Vertragingstijd (T)	Off 0 seconde On 0 seconde
Minimale schakeltijd	Switch-On 10 seconde
Aansluitwijze	Cable Clamp
Belastingswijze	ohmic, capacitive and inductive loads
Montagetype	Surface Mounted
Sensortype, opnemertype	Passive infrared
Uitvoering oppervlakte	Surface protection: Untreated Surface finishing: Matt
Materiaal	Material quality: Thermoplastic (3) Material: Plastic (3)
Verlichtingssterkte	0...1000 lx
Uitvoering klok	Movement sensor
RAL-nummer	RAL 9010 - Zuiverwit
Kleur	Alpine white
Battery Weight	0 g
Aantal batterijen	0

Environmental

Omgevingsluchttemperatuur	Operation -25 ... +55 °C
Beschermingsgraad	IP55
RoHS-status	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Dimensions

Product netto breedte	97 mm
Product netto hoogte	102 mm
Product netto diepte	105 mm
Product netto gewicht	0.185 kg
Inbouwdiepte (t ₂)	0 mm

Container Information

Pakketniveau 1 Units	carton 1 stuk
Pakketniveau 1 Breedte	100 mm
Pakketniveau 1 Hoogte	89 mm
Pakketniveau 1 Lengte	179 mm
Pakketniveau 1 Brutogewicht	0.32 kg
Pakketniveau 1 EAN	4011395079003
Pakketniveau 2 Units	10 stuk
Pakketniveau 2 Breedte	368 mm
Pakketniveau 2 Hoogte	102 mm
Pakketniveau 2 Lengte	510 mm
Pakketniveau 2 Brutogewicht	3.6 kg
Pakketniveau 3 Units	360 stuk

Pakketniveau 3 Breedte	0.8 m
Pakketniveau 3 Hoogte	0.107 m
Pakketniveau 3 Lengte	1.2 m
Pakketniveau 3 Brutogewicht	149.6 kg

Ordering

Minimale bestelhoeveelheid	1 stuk
Nummer douanetarief	85365080
Land van herkomst	Germany (DE)

Certificates and Declarations (Document Number)

Conformiteitsverklaring - CE	2CKA100000E1936
Instructies en handleidingen	DEBJE-ba_0373_1_6539_6845-Man
REACH Declaration	2CKA309999E9999
RoHS-informatie	9AKK104295D8727

Popular Downloads

Gegevensblad, technische informatie	No document needed
Instructies en handleidingen	DEBJE-ba_0373_1_6539_6845-Man

Classifications

ETIM 7	EC000133 - Movement sensor complete
ETIM 8	EC000133 - Movement sensor complete
WEEE-categorie	5. Small Equipment (No External Dimension More Than 50 cm)
AEEA B2C / B2B	Business To Consumer
CN8	8536 50 80
eClass	V11.0 : 27144007

Categorieën

Laagspanningsproducten en -systemen → StandAlone Electronics → Outdoor Movement Detector → ProfessionalLINE Series → Standard Devices → Watchdog 220 ProfessionalLINE

